



ICB-62M0550MAA

SKU: 231833



1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 5.0-50mm, Infrared, IP67

Abb. ähnlich

Main Features

-
- 1/2.8" Sony STARVIS CMOS Sensor
-
- Excellent light sensitivity
-
- Resolution max. 1920x1080 (Full HD)
-
- Motorised varifocal lens 5.0~50mm
-
- DOL-WDR (120dB) by triple scan images at 30/25fps
-
- Motion Detection, Privacy Zones, Slow Shutter
-

-
- Browser independent (IE, Edge, Safari, Firefox, Chrome)
-
- Smart Codec H.265 ROI (Region of Interest)
-
- Supports ONVIF Profile S and Profile T
-
- Vertical View 90°/270° Modus, H-Flip, Mirror
-
- Power supply PoE, IP67
-
- Integrated connection box including connection board
-

Specifications

Dimensions (HxWxD)	130,50x82,15x265,80mm
Series	eneo AN-Series, eneo Candid Small
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night Switch	ICR

ICB-62M0550MAA

Continuation of the specifications

Sensitivity	0,001 Lux
Sensitivity 2	40IRE, at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR, DOL-WDR 120dB
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	5 - 50 mm
Iris Control	DC
Zoom Factor	10x
Digital Zoom	yes
Horizontal Angle of View	49,9 - 8°
Vertical Angle of View	26,7 - 4,5°
Illumination	infrared
Housing	outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	aluminium
Blower	yes
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	motion detection, tampering protection
Mounting_4	ceiling mount, wall mount
Supply voltage	PoE
Power consumption	9W, PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-50°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP67
Camera built	Bullet
Remote configuration	web browser
Illumination range	approx. 40m
Weight	1.3kg
Manufacturer order number	231833

ICB-62M0550MAA

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4

Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update
211123	CUS-SL-B	Extra charge for special paint bullet camera in RAL color
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot

Your contact person

SLD Security & Communications Ltd.
101 Eden Grove Road
KT14 7PX Byfleet Surrey
GB
Tel: +44.7973112104
E-Mail: enquiries@sld.uk
Web: www.sld.uk



SLD Security & Communications
Secure by Design