



# ICB-62M2713MAA

SKU: 230801



1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 2.8mm, Infrared, IP67

Abb. ähnlich

## Main Features

- .....
- 1/2.8" Sony STARVIS CMOS Sensor
- .....
- Excellent light sensitivity
- .....
- Resolution max. 1920x1080 (Full HD)
- .....
- Motorised varifocal lens 2.7~13.5mm
- .....
- DOL-WDR (120dB) by triple scan images at 30/25fps
- .....
- Motion Detection, Privacy Zones, Slow Shutter
- .....

- .....
- Browser independent (IE, Edge, Safari, Firefox, Chrome)
- .....
- Smart Codec H.265 ROI (Region of Interest)
- .....
- Supports ONVIF Profile S and Profile T
- .....
- Vertical View 90°/270° Modus, H-Flip, Mirror
- .....
- Power supply PoE, IP67
- .....
- Integrated connection box including connection board
- .....

## Specifications

Dimensions (HxWxD)	130,50x82,15x265,80mm
Series	eneo AN-Series, eneo Candid Small
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night Switch	ICR

# ICB-62M2713MAA

## Continuation of the specifications

Sensitivity	0,0008 Lux
Sensitivity 2	40IRE, at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR, DOL-WDR 120dB
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	yes
Horizontal Angle of View	108 - 32°
Vertical Angle of View	56 - 18°
Illumination	infrared
Housing	outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	aluminium
Blower	yes
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	motion detection, tampering protection
Mounting_4	ceiling mount, wall mount
Supply voltage	PoE
Power consumption	8W, PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-50°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP67
Camera built	Bullet
Remote configuration	web browser
Illumination range	approx. 40m
Weight	1.25kg
Manufacturer order number	230801

# ICB-62M2713MAA

## Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4

## Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update
211123	CUS-SL-B	Extra charge for special paint bullet camera in RAL color
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot

## Your contact person

SLD Security & Communications Ltd.  
101 Eden Grove Road  
KT14 7PX Byfleet Surrey  
GB  
Tel: +44.7973112104  
E-Mail: [enquiries@sld.uk](mailto:enquiries@sld.uk)  
Web: [www.sld.uk](http://www.sld.uk)



SLD Security & Communications  
Secure by Design