



INP-75A0033MIA

SKU: 234751



Netzwerk Dome, PTZ, 33x 2952x1944, Tag/Nacht, WDR, AI Alarm, Audio, 24/12V, PoE, IP66

Main Features

1/2.7" CMOS sensor, maximum resolution 5 MP/30fps

AI analysis functions including object classification

WDR 120dB, 3D-DNR Noise Reduction

Motorized autofocus zoom lens 33x 4.3-142mm

Smart Codec H.265/H.264, multi-streaming

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Supports ONVIF Profile S and Profile T

Local storage via Micro SD card

Audio input and output

Power supply 12VDC, 24VAC or PoE IEEE 802.3at

IR LED illumination, IP66

Wall bracket included

Specifications

| | |
|-------------------------|--|
| Dimensions (HxWxD) | 206,4×351,8mm |
| Series | eneo IN-Series |
| Camera Type | Face recognition, People Count, Retail Intelligence |
| Resolution Standard | 5 Megapixel |
| System | True Day&Night |
| Sensor size | 1/2.7" |
| Imager | CMOS |
| Video compression | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG |
| Image resolution max. | 2592x1944 |
| Image Transmission Rate | 30 fps |

INP-75A0033MIA

Continuation of the specifications

| | |
|--------------------------|--|
| Day&Night Switch | ICR |
| Sensitivity | 0,003 Lux |
| Sensitivity 2 | at F1.6 |
| Low Speed Shutter | yes |
| Digital Noise Reduction | yes |
| Backlight Compensation | BLC, HLC |
| Wide Dynamic Range (WDR) | WDR 120dB |
| Motion Detector | yes |
| Lens Type 2 | auto focus zoom |
| Focal Length | 4,3 - 142 mm |
| Iris Control | DC |
| Digital Zoom | yes |
| Horizontal Angle of View | 55 - 2,3° |
| Vertical Angle of View | 41,6 - 1,7° |
| Illumination | infrared |
| Housing | outdoor |
| Color (housing) | black, Pantone P 179-1, RAL9003 |
| Housing material | aluminium |
| Heater | no |
| Blower | no |
| Rotation range | 360° |
| Speed (manual) | 0.6° to 200°/s°/Sek. |
| Speed (preset) | 0.6° to 200°/s°/Sek. |
| Alarm inputs | no |
| Alarm outputs | no |
| Audio support | yes |
| Ethernet interface | 100Base-TX, 10Base-T |
| Serial interfaces | Ethernet |
| Internal storage | microSDHC card, microSDXC card |
| Analysis functions | audio detection, Crowd detection, Face detection, face recognition, Heatmapping, intrusion, Line detection, Object classification (person / vehicle), Object left,removed, Queue management, trip wire detection with counting and direction detection |
| Mounting_4 | ceiling mount, wall mount |
| Supply voltage | 12VDC, PoE |
| Power consumption | 25,5W |
| Power over Ethernet | IEEE 802.3at |
| Vandal proof | no |
| Operating temperature | -30°C ~ +60°C, @ Humidity 90% or less (non-condensing) |
| ONVIF | ONVIF Profile G, ONVIF Profile S, ONVIF Profile T |

INP-75A0033MIA

Continuation of the specifications

| | |
|---------------------------|--|
| Protection rating | IP66 |
| Camera built | PTZ |
| Audio | 1/1 Line input and output, 2 Way Audio |
| Remote configuration | web browser |
| Illumination range | approx. 150m |
| Weight | 3.7kg |
| Manufacturer order number | 234751 |

Optional Accessory

| SKU | Name | Description |
|--------|-----------------------|---|
| 235562 | CM-22 | Corner mounting adapter for wall bracket WB-24 and PTZ dome camera INP-75A0033MIA |
| 218218 | eneo Site Manager | Management Software for eneo IP products |
| 236198 | IPC Installation Tool | Supports adjustments for cameras with AI features for IN-series |
| 235257 | PM-21 | Pole mounting adapter for camera connection box AK-20 and AK-21 |

Optional Services

| SKU | Name | Description |
|--------|---------------|--|
| 229234 | CON-KAM-IPKON | Preconfiguration 1x IP camera Function test, FW update |

Your contact person

SLD Security & Communications Ltd.
 101 Eden Grove Road
 KT14 7PX Byfleet Surrey
 GB
 Tel: +44.7973112104
 E-Mail: enquiries@sld.uk
 Web: www.sld.uk



SLD Security & Communications

Secure by Design