



IPD-52M2713MAA

SKU: 230800



1/2.8" Network Dome, Fix, 1920x1080, Day/Night, DOL-WDR, 2.7-13.5mm, Infrared, IP66

Main Features

-
- 1/2.8" Sony STARVIS CMOS Sensor
-
- Excellent light sensitivity
-
- Resolution max. 1920x1080 (Full HD)
-
- Motorised varifocal lens 2.7~13.5mm
-
- DOL-WDR (120dB) by triple scan images at 30/25fps
-
- Motion Detection, Privacy Zones, Slow Shutter
-

-
- Browser independent (IE, Edge, Safari, Firefox, Chrome)
-
- Smart Codec H.265 ROI (Region of Interest)
-
- Supports ONVIF Profile S and Profile T
-
- Vertical View 90°/270° Modus, H-Flip, Mirror
-
- Fix Dome Housing (metal), IP66
-
- Power supply PoE or 12VDC
-

Specifications

Dimensions (HxWxD)	136x117mm
Series	eneo AN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night Switch	ICR

IPD-52M2713MAA

Continuation of the specifications

Sensitivity	0,0008 Lux
Sensitivity 2	40IRE, at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR, DOL-WDR 120dB
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	yes
Horizontal Angle of View	108 - 32°
Vertical Angle of View	56 - 18°
Illumination	infrared
Housing	outdoor
Color (housing)	Light Cool Gray 1C
Housing material	aluminium
Window heater	no
Blower	yes
Video outputs	no
Alarm inputs	no
Alarm outputs	no
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	no
Analysis functions	motion detection, tampering protection
Mounting_4	ceiling mount, wall mount
Supply voltage	12VDC, PoE
Power consumption	12VDC, 8W, 8W, PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP66
Camera built	Dome
Remote configuration	web browser
Illumination range	approx. 40m
Weight	730g
Manufacturer order number	230800

IPD-52M2713MAA

Continuation of the specifications

Optional Accessory

SKU	Name	Description
232565	AK-12	Camera junction box for wall and ceiling mounting

Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update

Your contact person

SLD Security & Communications Ltd.
101 Eden Grove Road
KT14 7PX Byfleet Surrey
GB
Tel: +44.7973112104
E-Mail: enquiries@sld.uk
Web: www.sld.uk



SLD Security & Communications
Secure by Design