



MPP-72A0020MIA

SKU: 219809



1/2,8" HD Analogue Dome, PTZ, Day&Night, 20x, 4,7-94mm, WDR 1920x1080, Infrared, IP66

Main Features

- 1/2,8" Sony STARVIS CMOS-Sensor
- 20x Auto Focus Zoom, 4.7 ~ 94mm / 16x Digital
- Resolution max. 1920x1080 (Full HD)
- Separate outputs for HD signals and composite
- Signal formats: HD-TVI, AHD selectable, composite

- Real time WDR (Wide Dynamic Range) 25 / 30fps
- Integrated infrared lighting (up to 60m)
- 3D DNR noise reduction, auto-calibration
- Protected areas, Defog function
- Alarm inputs and outputs, 12VDC, IP66

Specifications

Dimensions (HxWxD)	208,3x182,4mm
Series	eneo COAXIZE
Resolution Pixels	1920x1080
Resolution Pixels	1280x720, 720x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night Switch	ICR
Sensitivity	0,35 Lux
Sensitivity 2	50 IRE, at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes

MPP-72A0020MIA

Continuation of the specifications

Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Lens Type 2	auto focus zoom
Focal Length	4,7 - 94 mm
Zoom Factor	20x
Digital Zoom	16x
Horizontal Angle of View	55,5 - 3°
Vertical Angle of View	32,4 - 1,7°
Illumination	infrared
Housing	Outdoor
Color (housing)	black, white
Housing material	Aluminium
Heater	no
Window heater	no
Blower	no
Rotation range	360°
Speed (manual)	380°/Sek.
Speed (preset)	380°/Sek.
Video outputs	AHD, composite (CVBS), HD-TVI
Alarm inputs	4
Alarm outputs	2
Serial interfaces	Coaxitron (HD Protocol), RS-485
Analysis functions	Defog, DIS (digital image stabilisation)
Mounting_4	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	18W
Vandal proof	no
Operating temperature	-20°C ~ +50°C
Protection rating	IP66
Signal format	AHD @ 2MP, Composite (FBAS), HD-TVI @ 2MP
Camera built	PTZ
Frame Rate	25/30fps @ 1920x1080p, 50/60fps @ 1280x720p
Aperture range (F)	F1.6~F3.0
Illumination range	approx. 60m
Weight	2.8kg
Manufacturer order number	219809

Optional Accessory

SKU	Name	Description
-----	------	-------------

MPP-72A0020MIA

Continuation of accessory

216209	DOME-WB2-W	Wall bracket for IED-63xx Metal series and IEP-63Mxx, MEP-62Mxx
221234	EDMC/CWB-1-W	Wall or Pendant Mount Kit white, for Dome Camera Series MPP-72xx, IPP-72xx
217652	KBD-2USB	System Keyboard with 3-Axis Joystick, Jog Shuttle, USB, RS-485, 12VDC,
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

Optional Services

SKU	Name	Description
229233	CON-KAM-AKON	Preconfiguration 1x analog camera Function test, FW update
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot
211124	CUS-SL-P	Extra charge for special paint PTZ dome or panoramic camera in RAL color

Your contact person

SLD Security & Communications Ltd.
 101 Eden Grove Road
 KT14 7PX Byfleet Surrey
 GB
 Tel: +44.7973112104
 E-Mail: enquiries@sld.uk
 Web: www.sld.uk



SLD Security & Communications

Secure by Design